MSDS MATERIAL SAFETY DATA SHEET

Oakwood Products, Inc 1741 Old Dunbar Road West Columbia, SC 29172 www.oakwoodchemical.com

Phone Numbers:

Product Information 803-739-8800 Transportation Emergency 800-451-8346 Outside the USA 760-602-8700

MATERIAL IDENTIFICATION

NAME: 4-Chlorobenzoyl isothiocyanate

CAS#: [16794-67-5] CAT#: 2526 For R&D use only.

HEALTH HAZARD INFORMATION

LACHRYMATOR CORROSIVE HARMFUL

Causes burns.

May have harmful effects if inhaled or swallowed.

Avoid prolonged exposure.

Do not breathe vapor.

Use caution when handling.

Exposure to any chemical should limited.

To the best of our knowledge, the health hazards of this material have not been fully investigated.

Material is for research and development purposes only.

EXPOSURE CONTROLS/PERSONAL PROTECTION

Avoid all direct contact with product.

Wear protective safety goggles.

Wear chemical-resistant gloves.

Wear protective clothing and boots.

Ensure ventilation during use.

After contact with skin, wash immediately.

FIRST AID

EYE CONTACT: Check for and remove any contact lenses. IMMEDIATELY flush Eyes with running water for at least 15 minutes while keeping eyes open. COLD water may be used. Seek medical attention.

SKÍN CONTACT: After contact with skin, wash with plenty of water. Gently and thoroughly wash the contaminated skin with running water and non-abrasive soap. COLD water may be used. Cover the irritated skin with an emollient. Seek medical attention. Wash any contaminated clothing before reusing.

<u>INHALATION</u>: Remove victim from source of exposure to fresh air. If breathing is difficult administer oxygen. Seek medical attention.

<u>INGESTION</u>: Do not induce vomiting. Give water to victim to drink. Seek medical attention.

Oakwood Products, Inc 1741 Old Dunbar Road West Columbia, SC 29172 Phone: (803) 739-8800

Fax: (803) 739-6957

FIRE MEASURES

Extinguishing media: carbon dioxide, dry chemical powder, alcohol or polymer foam. **Special fire-fighting procedures**: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes.

Unusual fire and explosion hazards/decomposition of product: emits toxic fumes under fire conditions.

HANDLING AND STORAGE INFORMATION

LACHRYMATOR
CORROSIVE
HARMFUL
AVOID PROLONGED USE
AVOID ALL DIRECT CONTACT WITH MATERIAL
Wash thoroughly after handling.

Do not breathe dust or vapor.

Have safety shower and eye wash available.

Do not get in eyes, on skin, on clothing.

Keep container tightly closed.

Store in a cool, dry, well-ventilated area.

Ensure adequate ventilation during use.

Use only in a chemical fume hood.

Avoid sources of ignition.

ACCIDENTAL RELEASE MEASURES

Steps to be taken if material is released or spilled: Wear appropriate respirator, rubber boots and heavy rubber gloves. Scoop up and place in an appropriate container. Ventilate area and wash spill site after pickup is complete. Wash skin immediately with plenty of water. Absorb on sand or vermiculite and place in closed containers for disposal.

DISPOSAL INFORMATION

Dissolve in or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber. Observe all Federal, State and local laws.

PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: light yellow solid

MF: C8H4CINOS

MW: 197.64 BP: no data MP: 45-46 $^{\circ}$ C DEN: no data N_d²⁰: no data FP: no data Oakwood Products, Inc 1741 Old Dunbar Road West Columbia, SC 29172 Phone: (803) 739-8800

Fax: (803) 739-6957

REACTIVITY DATA

INCOMPATIBILITIES: strong oxidizing agents, strong acids, and strong bases. HAZARDOUS DECOMPOSITION PRODUCTS: may evolve carbon monoxide, carbon dioxide, nitrogen oxides, sulfur oxides, and hydrogen chloride.

TOXICITY INFORMATION

ACUTE EFFECTS:

Corrosive

Harmful

May be harmful by ingestion and inhalation.

Material is irritating to mucous membranes and upper respiratory tract.

To the best of our knowledge, the toxicological properties of this product have not been fully determined.

TRANSPORT INFORMATION

DOT

Corrosive solids, n.o.s.

8

UN1759 III

IMDG

Corrosive solid, n.o.s. 8
UN1759 III
EMS-No: F-A, S-B
Marine Pollutant: No

IATA

Corrosive solid, n.o.s.

8

UN1759 III

The above information is believed to be correct but does not purport to be all-inclusive and shall be used only as a guide. Oakwood shall not be held liable for any damage resulting from handling or from contact with the above product.